



Dig. Indicator 25,4x0,001 mm with ABS/TOL/Min/Max funktion

10356325

Digital precision dial gauge diameter $\varnothing 56$ mm with metal housing and hardened and ground $\varnothing 8$ mm h6 clamping shaft.

With switch mm / inch, ABS/INC, tolerance, zerosetting and with flat back. Dial indicator can be used in conjunction with USB data capture that delivers all test results to the optional program at your workplace. With flat back plate, lug included.

Reading: 0.001mm. Measuring range: 0-25.4 mm.

Delivered in a plastic box.

Battery: 1xCR2032 included.

- Metal housing
- $\varnothing 8$ mm h6 clamping shaft
- ABS
- Flat back plate with lug included

Product details

| | |
|----------------|---------------|
| Item no. | 10356325 |
| EAN | 5708004010357 |
| Customs tariff | 9017809000 |
| Sales Quantity | 1 |

Product specifications

| | |
|-----------------|-----------------------|
| Barcode | 5708004010357 |
| Resolution | 0,001 mm |
| Backside | Flat cover |
| Battery | 1xCR2032 |
| Data output | Yes |
| Diameter | $\varnothing 56$ mm |
| Measuring range | 0-25,4 mm |
| Accuracy | 0,004 mm |
| Product type | Digital indicator |
| Shank | $\varnothing 8$ mm h6 |
| Gross weight | 0.340 kg |
| Net weight | 0.150 kg |