



## Digital multimeter AC/DC 600V/10A w/protective rubber

15130710

A good and robust multimeter, encapsulated in rubber cover, with auto/manual range selection, max-hold and data hold. The instrument measures voltage, current, frequency, resistance, diode test and continuity. Complies with IEC 61010-1 CAT III 600V.

*Delivered incl. test leads.*

*Battery: 9V included.*

### Product details

Item no.	15130710
EAN	5708004054764
Customs tariff	9030310000
Sales Quantity	1

### Product specifications

Barcode	5708004054764
Working temperature	-20°C ~ 1000°C/ -4°F ~ 1832°F
Battery	9V
Dimensions	140x67x30xmm
Display type	LCD
Frequency Range	20kHz
Range Voltage DC	200mV/2V/20V/200V/600V
Max. display	2000
Resistance Range	200Ω/ 2kΩ/ 20kΩ/ 200kΩ/ 2MΩ/ 20MΩ
Accuracy Voltage AC	±(1,0%+3)
Accuracy Voltage DC	±(1,2%+3) / ±(1,2%+5)
Accuracy Current AC	±(1,2%+3) / ±(1,2%+5)
Accuracy Current DC	±(1,2%+3) / ±(3,0%+3)
Range Current AC	200μA/ 2mA/ 20mA/ 200mA/ 10A
Range Current DC	200μA/ 2mA/ 20mA/ 200mA/ 10A
Range Voltage AC	2V/20V/200V/600V
Safety directive	EN61010-1, 2-030, EN61010-2- 033, EN61326-1, CAT. III 600V
Product size	140 x 67 x 30 mm
Gross weight	0.320 kg
Net weight	0.270 kg