



Permanent lifting magnet 600/300 kg NEO600

30274600

It easily handles flat, round, and cylindrical loads with emphasis on safety and convenience. We test each individual magnet for break-away force with an air gap to simulate real operating conditions. The magnet body is highly resistant to mechanical damage, the bearings are secured, so their life span is longer. The magnet features a versatile lifting eye design for easy suspension. The magnet enables load handling at a maximum temperature of 80° C.

- Nominal lifting capacity for flat material: up to 600 kg
- Nominal lifting capacity for round material: up to 300 kg
- Temperature: max. 80° C
- Safety factor: 3+ (tested according to EN 13155)
- Handling flat, round, and cylindrical workpieces
- Lifting of profiled sections and sheets

Product details

| | |
|----------------|---------------|
| Item no. | 30274600 |
| EAN | 5708004054429 |
| Customs tariff | 8505110099 |
| Sales Quantity | 1 |

Product specifications

| | |
|------------------------------|----------------|
| Barcode | 5708004054429 |
| Width | 120 mm |
| Height | 180 mm |
| Length | 246 mm |
| Magnet force flat objects | 600 kg |
| Magnetic force round objects | 300 kg |
| Maximum heat exposure | 80° C |
| Min. / Max. diameter | 65/270 mm |
| Product type | Lifting magnet |
| Gross weight | 21.890 kg |
| Net weight | 19.000 kg |