



## Portable dynamic hardness for scales HL-HRC-HRB-HB-HS-HV

15247300

This integrated hardness tester, with OLED screen, is suitable for all metallic materials in hardness scale HL, HRC, HRB, HV, HB, HS.

The hardness tester can i.a. used on mold cavities, bearings and other mass-produced parts on the production line.

**Target range:** HL 174-900-HRC 19.6-68.0-HRB 13.5-101.7-HS 32.5-99.5-HB 20-655-HV 80-940

**Accuracy:** +/- 0.5% at 800 HLD

**Memory:** up to 200 data on 10 files

**Probe:** TYPE D

**Battery:** 4 x AA Rechargeable batteries

Delivered in transport box.

### Contains:

- OLED 128 x 64mm
- USB Port for data transfer
- Certified Standard test block in steel. (HLD)
- Cleaning brush
- Charger
- User manual
- Software and cable
- Calibration certificate
- Transport box

**IMPORTANT:** In order to operate the instrument correctly, the operating instructions should be read before use.

### Product details

Item no.	15247300
EAN	5708004032922
Customs tariff	9024104000
Sales Quantity	1

### Product specifications

Barcode	5708004032922
Working temperature	-20°C~ +50°C
Battery	4 x AA
Memory	200 data on 10 files
Accuracy	+/-0,5% ved 800 HLD
Product size	158 mm (L) X 41 mm (W) X 26 mm (H)
Gross weight	3.260 kg
Net weight	0.120 kg