



SYLVAC Digital Dial Indicator S_DIAL TEST SMART 0,8/2,0 x 0,001 mm IP54 (805.4323) BT (COMBI MODEL)

SYL8054323

S_Dial TEST Smart with completely new internal mechanics that ensures direct transmission and thus eliminates hysteresis errors. With IP54 enclosure class, the instrument is perfect for use in harsher workshop environments.

COMBI models with replaceable key points (12.5 mm + 36.5 mm can be used on one and the same housing).

Battery: 1xCR2032 included.

- Data outout: Bluetooth and proximity to USB/RS232
- Digital and analog display
- Water and coolant resistant IP54
- Automatic switch OFF
- Stem Ø 8 mm and dovetail back
- Rotating display over 360°
- Calibration certificate included

Product details

Item no.	SYL8054323
EAN	7640125689235
Customs tariff	90173020
Sales Quantity	1

Product specifications

Barcode	7640125689235
Resolution	0,001mm
Battery	CR2032
Data output	Bluetooth/USB/RS232
Diameter	Ø45,3 mm
Probe length	12,5 mm + 36,5 mm
Repeatability	1 µm
IP Class	IP54
Measuring range	0,8 mm + 2,0 mm
Accuracy	3 µm + 8 µm
Scale	0,001 mm
Gross weight	0.140 kg
Net weight	0.140 kg