



SYLVAC Digital Dial Indicator S_DIAL TEST SMART 2,0 x 0,001 mm IP54 key length 36,5 mm (805.4322) BT

SYL8054322

S_Dial TEST Smart with completely new internal mechanics that ensures direct transmission and thus eliminates hysteresis errors. With IP54 enclosure class, the instrument is perfect for use in harsher workshop environments.

Available in three different models with a key length of 12.5 mm or 36.5 mm and a model with replaceable key points (12.5 mm + 36.5 mm can be used on one and the same housing).

Battery: 1xCR2032 included.

- **Data output:** Bluetooth and proximity to USB/RS232
- Digital and analog display
- Water and coolant resistant IP54
- Automatic switch OFF
- Stem Ø8 mm and dovetail back
- Rotating display over 360°
- Calibration certificate included

Product details

Item no.	SYL8054322
EAN	7640125689204
Customs tariff	90173020
Sales Quantity	1

Product specifications

Barcode	7640125689204
Resolution	0,001 mm
Battery	CR2032
Data output	Bluetooth/USB/RS232
Diameter	Ø45,3 mm
Probe length	36,5 mm
Repeatability	1 µm
IP Class	IP54
Measuring range	2,0 mm
Accuracy	8 µm
Scale	0,001 mm
Gross weight	0.150 kg
Net weight	0.150 kg