



SYLVAC Digital Indicator S_DIAL WORK ADVANCED 100 x 0,01 mm IP54 (805.5641)

SYL8055641

SYLVAC IP54 Digital Indicator S_Dial Work Advanced.

Battery: 1xCR2032 included.

- Data output Proximity til USB/RS232
- Robust construction
- Water and coolant resistant
- New technology with configurable menus
- Broad choice of functions (MIN/MAX/DELTA, TOL, Factor, PRESET, AUTO OFF, etc.)
- Automatic wake-up and sleeping mode (Absolute System SIS)
- Maximum error of 3 µm

Product details

| | |
|----------------|---------------|
| Item no. | SYL8055641 |
| EAN | 7640125025354 |
| Customs tariff | 90173020 |
| Sales Quantity | 1 |

Product specifications

| | |
|--------------------|---------------------------|
| Barcode | 7640125025354 |
| Resolution | 0,01 mm |
| Battery | CR2032 |
| Data output | USB / RS232 |
| Diameter | Ø59,5 mm |
| Error limit | 20 µm |
| Repeatability | 2 µm |
| IP Class | IP54 |
| Measuring range | 0-100 mm |
| Model | S_Dial Work Advanced |
| Accuracy | 2 µm |
| Product type | Digital indicator |
| Programmable by PC | Yes (via Sylcom software) |
| Shank | Ø8 h6 |
| SYLVAC item no. | 805-5641 |
| Brand name | SYLVAC |
| Gross weight | 0.380 kg |
| Net weight | 0.380 kg |