



SYLVAC Digital Indicator S_DIAL WORK ANALOG 12,5 x 0,001 mm IP54 (805.5307)

SYL8055307

SYLVAC Digital Indicator S_Dial WORK ANALOG.

Battery: 1xCR2032 included.

- Data outputs Power and Proximity or Bluetooth® (depends on model)
- Adaptive analog display (up to 0.2 µm per segment)
- Robust construction
- Water and coolant resistant
- New technology with configurable menus
- Broad choice of functions (MIN/MAX/DELTA, TOL, Factor, PRESET, AUTO OFF, etc.)
- Automatic wake-up and sleeping mode, Absolute System S.I.S

Product details

| | |
|----------------|---------------|
| Item no. | SYL8055307 |
| EAN | 7640125026054 |
| Customs tariff | 90173020 |
| Sales Quantity | 1 |

Product specifications

| | |
|--------------------|----------------------------|
| Barcode | 7640125026054 |
| Resolution | 0,001 mm |
| Backside | Flat cover |
| Battery | CR2032 |
| Data output | USB / RS232 |
| Diameter | Ø59,5 mm |
| Error limit | 3 µm |
| Repeatability | 2 µm |
| IP Class | IP54 |
| Measuring range | 0-12,5 mm |
| Model | S_Dial WORK ANALOG |
| Accuracy | 2 µm |
| Product type | Digital Indicator |
| Programmable by PC | Yes (with Sylcom software) |
| Shank | Ø8 h6 |
| SYLVAC item no. | 805-5307 |
| Brand name | SYLVAC |
| Gross weight | 0.120 kg |
| Net weight | 0.120 kg |