



SYLVAC Digital Indicator S_DIAL WORK BASIC 25 x 0,01 mm IP51 (805.1401)

SYL8051401

Can be used with Sylcom software. Data output: USB / RS232.
Functions: Min/Max/Delta, Preset (max. 99.999), conversion factor, reset.

Battery: 1xCR2032 included.

- Data output Proximity til USB/RS232
- Robust construction
- Water and coolant resistant
- Standard functions (mm/inch, preset, direction of measurement)
- Automatic wake-up and sleeping mode (Absolute System SIS)

Product details

Item no.	SYL8051401
EAN	7640125026245
Customs tariff	90173020
Sales Quantity	1

Product specifications

Barcode	7640125026245
Resolution	0,01 mm
Battery	CR2032
Data output	USB / RS232
Diameter	Ø59,5 mm
Error limit	10 µm
Repeatability	2 µm
IP Class	IP51
Measuring range	0-25 mm
Accuracy	2 µm
Product type	Digital måleur
Shank	Ø8 h6
SYLVAC item no.	805-1401
Brand name	SYLVAC
Resolution	0,01 mm
Battery	CR2032
Data output	USB/RS232
Error limit	10 µm
Repeatability	2 µm
IP Class	IP51
Measuring range	0-25 mm
Gross weight	0.230 kg