



## X300 Coating thickness gauge 0-3000μm external probe Bluetooth to App Xthick

15079530

X300 Coating Thickness Gauge 0-3000μm with External Probe, Bluetooth to XThick App

Flexible coating thickness gauge with an external ruby probe combining Fe + NFe, making it suitable for measurements in confined spaces. It is used for measuring, for example, paint and coating thicknesses on both magnetic and non-magnetic metals. For instance, it measures galvanizing, paint, zinc, plastic coating, aluminum, copper, and more.

### Features:

- Measuring paint thickness on cars, ship repairs, galvanizing, and measuring felt thickness, etc.
- External combined probe (Fe) 0-3000μm for iron, stainless steel + (NFe) 0-3000μm for aluminum and copper
- The instrument has automatic substrate recognition.
- Accuracy:  $\pm 2\% + 1\mu\text{m}$  under 2000μm /  $\pm 3\% + 2\mu\text{m}$  up to 3000μm.
- Measurement units: μm, mm, inches.
- Measures galvanizing, paint, zinc, aluminum, copper, plastic coatings.
- Supports zero calibration.
- Suitable for measurements in confined spaces.
- Automatic rotating screen.

### Product details

Item no.	15079530
EAN	5708004008415
Customs tariff	9017300000
Salgsenhed	Pc.

### Product specifications

Resolution	0.1μm (0~99.9μm); 1μm (≥100μm)
Measuring range	0-3000 μm
Accuracy	±(2%+1μm)
Gross weight	0.570 kg
Net weight	0.470 kg